



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



RECESSED ACCESS DOOR AP-5010

Application

- Designed for use in acoustical plaster walls and ceilings

Product Features

- Door is recessed 5/8" and is lined with self-furring lath
- Expansion casing bead with 3" wide galvanized lath

AP-5010 Access Door Specifications:

Material: Steel or Stainless Steel: 16 gage door, 14 gage mounting frame

Door: Recessed 5/8" and lined with self-furring galvanized lath

Door Frame: Expansion casing bead with 3" wide galvanized lath, recessed 3/4" to receive plaster

Hinge: Concealed, pivoting rod type. (For wall applications, a continuous exposed piano hinge is suggested.)

Standard Latch: Flush to surface, screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock and key, allen head cam latch, spanner head cam latch

Finish: Steel: 5-stage iron phosphate preparation with prime coat of White alkyd baking enamel



AVAILABLE SIZES (Special sizes available upon request)

| NOMINAL DOOR SIZE W X H | | WEIGHT PER DOOR | | |
|-------------------------|-----------|-----------------|------|------|
| inches | mm | Latches | lbs. | kg. |
| 12 X 12 | 305 X 305 | 1 | 8.5 | 3.9 |
| 18 X 18 | 457 X 457 | 2 | 15 | 6.8 |
| 24 X 24 | 610 X 610 | 2 | 23 | 10.4 |
| 24 X 36 | 610 X 914 | 4 | 30 | 13.8 |

Wall or ceiling opening is $W + 3/8"$ (9 mm)
For detailed specifications see submittal sheet

