

**DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE****1. PRODUCT AND COMPANY IDENTIFICATION**

Dow Corning Corporation  
South Saginaw Road  
Midland, Michigan 48686

**24 Hour Emergency Telephone: (989) 496-5900**

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 04005047

Revision Date: 2013/02/20

Generic Description: Silicone elastomer

Physical Form: Paste

Color: See product name

Odor: Slight odor

NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

**2. HAZARDS IDENTIFICATION****POTENTIAL HEALTH EFFECTS****Acute Effects**

- Eye: Direct contact may cause mild irritation.
- Skin: No significant irritation expected from a single short-term exposure.
- Inhalation: No significant effects expected from a single short-term exposure.
- Oral: Low ingestion hazard in normal use.

**Prolonged/Repeated Exposure Effects**

- Skin: Repeated or prolonged exposure may cause irritation.
- Inhalation: No known applicable information.
- Oral: Repeated ingestion or swallowing large amounts may injure internally.

**Other Health Effects**

This product contains a chemical(s) that has the following effect(s):  
Carcinogenicity

See Section 11 for specific details.

**DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE****Signs and Symptoms of Overexposure**

No known applicable information.

**Medical Conditions Aggravated by Exposure**

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
68186-85-6	<=0.2	Cobalt titanite green spinel

The above components are hazardous as defined in 29 CFR 1910.1200.

**4. FIRST AID MEASURES**

Eye:	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelid(s) open. Obtain medical attention.
Skin:	No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
Inhalation:	If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Oral:	If irritation or discomfort occur, obtain medical advice.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

**5. FIRE FIGHTING MEASURES**

Flash Point:	Not applicable.
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.

**DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
 SANDSTONE**

Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO <sub>2</sub> ), dry chemical or water spray. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire Hazards:	None.

**6. ACCIDENTAL RELEASE MEASURES**

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

**7. HANDLING AND STORAGE**

Use with adequate ventilation. Traces of benzene (carcinogen) may form if heated in air above 300°F (149°C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements. Avoid eye contact. Avoid skin contact. Do not take internally.

Use reasonable care and store away from oxidizing materials. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Component Exposure Limits**

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
68186-85-6	Cobalt titanite green spinel	Observe limits: Nickel - OSHA PEL and ACGIH TLV: TWA 1 mg/m <sup>3</sup> . Cobalt - OSHA PEL (final rule) and ACGIH TLV:

DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE

TWA 0.05 mg/m3.

**Engineering Controls**

Local Ventilation: None should be needed.  
General Ventilation: Recommended.

**Personal Protective Equipment for Routine Handling**

Eyes: Use proper protection - safety glasses as a minimum.  
Skin: Washing at mealtime and end of shift is adequate.  
Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.  
Inhalation: No respiratory protection should be needed.  
Suitable Respirator: None should be needed.

**Personal Protective Equipment for Spills**

Eyes: Use proper protection - safety glasses as a minimum.  
Skin: Washing at mealtime and end of shift is adequate.  
Inhalation/Suitable Respirator: No respiratory protection should be needed.  
Precautionary Measures: Avoid eye contact. Avoid skin contact. Do not take internally. Use reasonable care.  
Comments: Traces of benzene (carcinogen) may form if heated in air above 300°F (149°C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical Form: Paste  
Color: See product name  
Odor: Slight odor  
Specific Gravity @ 25°C: 1.52

**DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE**

Viscosity: Not determined.  
Freezing/Melting Point: Not determined.  
Boiling Point: Not determined.  
Vapor Pressure @ 25°C: Not determined.  
Vapor Density: Not determined.  
Solubility in Water: Not determined.  
pH: Not determined.  
Volatile Content: Not determined.  
Flash Point: Not applicable.  
Autoignition Temperature: Not determined.  
Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**10. STABILITY AND REACTIVITY**

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

**Hazardous Decomposition Products**

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Formaldehyde. Silicon dioxide. Quartz. Nitrogen oxides. Sulfur oxides.

**11. TOXICOLOGICAL INFORMATION****Component Toxicology Information**

Inhalation of fumes may result in metal fume fever, a flu-like illness with symptoms of metallic taste, fever and chills, aches, chest tightness, and cough.

Prolonged overexposure to quartz or crystalline silica dust causes fibrotic lung disease (silicosis) and potentially lung cancer.

Octamethylcyclotetrasiloxane administered to rats by inhalation at concentrations of 500 and 700 ppm resulted in statistically significant decreases in the number of pups born and the live litter size in both the first and second generations. Prolonged estrous cycles, and decreased mating and fertility indices were observed following 700 ppm

DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE

exposure in the second generation only. There were also increases in the incidence of deliveries of offspring extending over an unusually long time period (dystocia).

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only.

Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans.

Based on the available information on its potential to cause harm to human health, Health Canada, in a 2008 screening assessment, has concluded that octamethylcyclotetrasiloxane is not entering the environment in a quantity or concentration or under conditions that constitute or may constitute a danger in Canada to human life or health ([http://www.ec.gc.ca/substances/ese/eng/challenge/batch2/batch2\\_556-67-2.cfm](http://www.ec.gc.ca/substances/ese/eng/challenge/batch2/batch2_556-67-2.cfm)).

Repeated exposure in rats to D4 resulted in what appears to be protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

**Special Hazard Information on Components****Carcinogens**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
68186-85-6	<=0.2	Cobalt titanite green spinel	IARC Group 2B - Possibly Carcinogenic to Humans. Cobalt compound.

**12. ECOLOGICAL INFORMATION****Environmental Fate and Distribution**

Complete information is not yet available.

**Environmental Effects**

Complete information is not yet available.

**Fate and Effects in Waste Water Treatment Plants**

Complete information is not yet available.

## Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100

DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE

Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000
----------------------------	-------	------------------	-------

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

**13. DISPOSAL CONSIDERATIONS****RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

**14. TRANSPORT INFORMATION****DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

**Ocean Shipment (IMDG)**

Not subject to IMDG code.

**Air Shipment (IATA)**

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

**15. REGULATORY INFORMATION**

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**EPA SARA Title III Chemical Listings****Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

**Section 304 CERCLA Hazardous Substances (40 CFR 302):**

None.

DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE**Section 311/312 Hazard Class (40 CFR 370):**

Acute: No  
 Chronic: Yes  
 Fire: No  
 Pressure: No  
 Reactive: No

**Section 313 Toxic Chemicals (40 CFR 372):**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
68186-85-6	<=0.25	Cobalt titanite green spinel

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

**Supplemental State Compliance Information****California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
13463-67-7	<=5.8000	Titanium dioxide
67-56-1	<0.1000	Methyl alcohol Developmental toxin.

**New Jersey**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate
70131-67-8	<=41.0	Dimethyl siloxane, hydroxy-terminated
63148-62-9	<=17.0	Polydimethylsiloxane
147-14-8	<=9.2	Pigment Blue 15
1333-86-4	<=6.3	Carbon black
13463-67-7	<=5.8	Titanium dioxide



DOW CORNING(R) CONTRACTORS WEATHERPROOFING SEALANT,  
SANDSTONE

14808-60-7	<1.0	Quartz
68186-85-6	<=0.2	Cobalt titanite green spinel

**Pennsylvania**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate
70131-67-8	<=41.0	Dimethyl siloxane, hydroxy-terminated
63148-62-9	<=17.0	Polydimethylsiloxane
147-14-8	<=9.2	Pigment Blue 15
1333-86-4	<=6.3	Carbon black
1332-37-2	<=5.9	Iron oxide
13463-67-7	<=5.8	Titanium dioxide
112945-52-5	3.0 - 7.0	Amorphous fumed silica

**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark