



ENERFoam®

THE PROFESSIONAL POLYURETHANE GUN FOAM SYSTEM



- Thermal and sound insulation
- Seals windows and doors
- Blocks insects and rodents
- Acoustical sealant – STC of 69
- Drywall Adhesive
- Fast foam application with less fatigue using foam dispensing tool



• Ener42 with Ener15 Gun

- Replaces up to 40 quart tubes of traditional caulk or adhesive.
- Fast curing. Foam can be trimmed in less than one hour. Initial skin time is less than six minutes! Faster than any other foam.
- Unique mechanical valve. Spring loaded for reuse. Won't glue shut after use.
- Contains no solvents. Compatible with EPS foamboard.
- Use as drywall adhesive. Meets ASTM C557-93, CGSB 71.25. Also meets CA25-4 (Adhesive For Structural Use in the Manufacture of Mobile Homes & Commercial Coaches).
- Less mudding labor. Fewer "nail pops." Reduces callbacks.
- Available in two sizes: Ener25 – 24oz. (680g), Ener42 – 32oz. (908g).

(3 6 2 6)

1.800.800.FOAM

www.polyurethanesystems.com



THE DOW CHEMICAL COMPANY

* Trademark of The Dow Chemical Company



THE PROFESSIONAL GUN FOAM SYSTEM

More Benefits!

■ Minimal Expansion

Great for sealing around windows and doors.

■ Elastic Properties

Foam will expand and compress with the shifting of structures from winter to summer. EnerFoam will not crack like rigid foams.

■ Works in Temperatures of 25°F to 120°F (-4°C to 49°C)

EnerFoam stored at room temperature can be dispensed in a wide temperature range. Many other brands only work in 60°F to 90°F (16°C to 32°C).

■ Low Maintenance Applicator Tool

Professional applicator tool available in three models: (Standard tool, 24" barrel and 42" barrel). Allows applicator to access those hard-to-reach places without standing on a ladder.

■ Insulator, Air Barrier, Acoustical Sealant

R-value of 5.7 (more than most windows themselves). Acoustical rating of 69 STC.

■ Standards & Independent Tests

- ASTM C557-93 "Adhesives for Fastening Gypsum Wallboard to Wood Framing." CGSB 71.25 "Canadian Drywall Adhesive Standard."
- CA25-4 "Standard for the Evaluation of Adhesives for Structural Use in the Manufacturer of Mobile Homes and Commercial Coaches."



• Ener25 with Ener15 Gun

OTHER GREAT PRODUCTS...



■ EnerFoam® – The Professional Foam System

Because of its versatility, the EnerFoam Professional Foam System has established itself as the premier polyurethane foam available to professionals. EnerFoam is ideal for applications including insulation, hole and crack filling, blocking insects, acoustical sealing (STC 69), and is the perfect adhesive for insulating concrete forms. EnerFoam's high yield saves professionals both time and money.

■ EnerBond® DW – Drywall Adhesive

EnerBond DW, the first single-component foam designed as a drywall adhesive, is used to adhere regular and vinyl-faced wallboard to wood or steel studs, masonry, and other structurally sound surfaces. One can of EnerBond DW replaces up to 40 quart tubes of traditional adhesives and enables the contractor to use up to 66 percent fewer fasteners, reduce call backs and nail "pops," decrease mudding labor, and lower material costs. Solvent-free EnerBond DW exceeds ASTM C557-93 and conforms to CGSB 71.25.

■ EnerBond® SF – Subfloor Adhesive

EnerBond SF is specifically formulated for subfloor and drywall applications. Compatible with lumber, concrete, drywall, masonry and metals. One can of EnerBond SF replaces up to 15 quart tubes of traditional adhesives. This solvent-free adhesive reduces squeaks, withstands temperature extremes and exceeds all major glued subfloor standards (APA-AFG-01, ASTM D3498 and CGSB 71.26).

■ EnerBond® MH – Manufactured Housing Adhesive

EnerBond MH is a specially formulated adhesive technology for Manufactured Housing and Modular Construction. EnerBond MH helps eliminate squeaks in subfloors and loose panels in drywall applications. The adhesive can be used for both vertical and table applications. EnerBond MH exceeds CA25-4, APA-AFG-01, ASTM D3498, CGSB 71.25 and ASTM C557-93.

■ EnerFoam® 10 & 16 Pounders

EnerFoam 10 & 16 Pounders are formulated to save energy by sealing windows and doors, stopping drafts, blocking insects and rodents, and stopping leaks. These fully paintable foams are tack-free in 10 minutes, can be trimmed in two hours, and bond to wood, concrete, brick and most plastics. EnerFoam 10 & 16 Pounders are dispensed in bead form using the adjustable foam dispenser and make sealing fast, easy and economical.

■ EnerFoam® II – Two-Component Kits

EnerFoam II is the ideal solution for a professional's large application needs. Perfect for filling large holes and gaps, this two-component, self-controlled, portable kit is dispensed through a spray nozzle. EnerFoam II provides superior insulation for all projects and gives professionals the benefits of being moisture-resistant, paintable and solvent-free. EnerFoam II is available in two sizes.



THE DOW CHEMICAL COMPANY

1881 West Oak Parkway, Marietta, GA 30062

1.800.800.3626 • www.polyurethanesystems.com