



RED STUCCO TAPE

Within construction environments, stucco applications require consistently high performing tapes that can withstand the rigors and use conditions they are subjected to by application equipment, trim work and surface protection applications.

Demand Products' LMR2 Red Stucco Tape is a premium and reliable, UV resistant tape for demanding masking applications and use conditions.

Our Red Stucco Tape is widely regarded in the construction

industry as a specialty product with proven performance including superior adhesion, excellent durability and strength, ease of use and watertight sealing properties.

Demand Products has extensive experience in supplying the EIFS/Stucco market segment with Red Stucco Tape and is highly regarded in this field. Our manufacturing facility is established as the global center of excellence for PE tape manufacturing with unrivaled technical capabilities.



DEMAND[™]
P R O D U C T S INC.

LMR2 | RED STUCCO TAPE

Key Features and Benefits:

- Aggressive adhesive for superior bonding and heavy duty protection
- Ideal for external environments such as construction sites and other high UV exposure applications
- Immediate and long term adhesion to a wide range of surfaces and substrates
- Premium rubber based adhesive formulation allows clean peel of tape, even after extended periods
- Creates water tight seal and provides humidity resistance in all weather and climate conditions
- Excellent tensile strength and product flexibility for rough surfaces, awkward shaped objects and angles

- Available with straight edges for a perfect clean line finish
- Longer service life than traditional tape options
- Does not leave adhesive residue
- Red color for ease of identification and on site visibility

Construction Applications:

- Temporary masking of door and window frames within construction sites
- Masking of wood, vinyl, metal and tiles during painting processes



LMR2

Product Specifications:

LMR2 Red Stucco Tape is a 7 mils / 0.18 mm thick specialty PE film tape, coated with a specially developed rubber based adhesive and with additional UV resistance.

Recommended Product: LMR2 Red Stucco Tape

Product	Adhesion to Backing (N/25mm)	Adhesion to Steel (N/25mm)	Tensile Strength (N/25mm)	Additional Properties	Brand	Widths(mm)	Length(m)	Color
LMR2	8.9	20.9	96	Short term UV Resistance Straight edge	Demand Products	48 / 72	33	Red

This information is provided by Demand Products for information only. The information is considered to be reliable but accuracy is not guaranteed. Any results shown in this information may not be relevant to all users of the product and it is the user's responsibility to determine the suitability of the product for its intended purpose. Demand Products expressly disclaims all express or implied warranties including merchantability and fitness for a particular purpose to the fullest extent permitted by law and does not accept responsibility or liability (whether direct, indirect or consequential) arising from use of the product or reliance on the information. Demand Products does not exclude liability for death or personal injury arising from its negligence or fraud.

