

**PRO-LOK**<sup>™</sup> Foam to Foam Adhesive

**PRO-LOK**<sup>™</sup> is a fast cure, low expansion polyurethane foam adhesive with excellent adhesion properties for wood, stone, gypsum board, glass, mosaic, brick, cement board, EPS and XPS foam panels.

**APPLICATION CONDITIONS:**

Usage temperature between 40°F (5°C) and 95°F (35°C). The cured foam temperature endurance -40°F (-40°C) and ~248°F (120°C).

Not suitable for structural bonding. This product is not intended to replace mechanical fasteners. For best results, use **PRO-LOK**<sup>™</sup> in conjunction with PBH, DP300 or DP400 washers.

**SAFETY:**

Keep Out of Reach of Children.

Keep Upright.

Shelter from direct sunlight.

Do not expose to temperatures above 120°F (50°C).

Do not pierce or burn cannister even after use.

Do not smoke or expose to open flame during the application process.

Appropriate eye protection and gloves should be used during application.

**DIRECTIONS:**

1. Shake can well.
2. Surface must be clean and free of dust and grease.
3. Screw foam dispensing gun on tightly and turn can upside down.
4. Fill vertical gaps from the bottom upwards.
5. **PRO-LOK**<sup>™</sup> is tack-free (dry to the touch) in approximately 8 minutes in temperatures between 65°F (18°C) and 77°F (25°C). Cure time depends on temperature and humidity conditions.
6. Remove fresh **PRO-LOK**<sup>™</sup> overspray with appropriate cleaner or solvents. Cured **PRO-LOK**<sup>™</sup> can only be removed manually.

Note: This product requires foam dispensing gun for application (sold separately). Use **PRO-KLEAN**<sup>™</sup> FOAM CLEANER to clean dispenser after use.

**LIMITED WARRANTY:** Buyer agrees that if the product proves to be defective, DEMAND PRODUCTS' only obligation shall be to replace or refund the purchase price of such product. DEMAND PRODUCTS shall not be liable in tort or contract for any loss or damage, direct, incidental or consequential. The information and suggestion for use contained herein are believed to be accurate, but are not to be construed as warranties. User shall determine the suitability of the product for his or her intended use and shall assume all risk associated therewith.

**CAUTION:** Flammable. Vapors are harmful. Vapors released by this product can be easily ignited and may burn explosively. May cause skin, eye or respiratory irritation, dizziness, headaches, nausea and in extreme cases, unconsciousness or death. Overexposure may cause central nervous system depression. Chronic overexposure may cause peripheral nerve damage. Avoid breathing vapors, ingesting, skin or eye contact. Do not store at temperatures above 100°F/38°C or in direct sunlight. Avoid contamination of food. Do not puncture or incinerate container. Fire can be contained with CO<sub>2</sub>, sand and dry chemical.

**STORAGE and HANDLING:** Store vertically in a controlled environment between 60°F/16°C and 100°F/38°C and away from direct sunlight. Use approved equipment for transportation of container to avoid puncturing or rupturing of container. Clean up spillage with floor cleaning compound or suitable absorbents. Clean spill area with detergent and water. Shelf life is up to 18 months when stored under proper conditions in a cool dry place.