

1 DESCRIPTION

Durable, moisture resistant PE (polyethylene) film backing with a synthetic rubber-based pressure-sensitive adhesive. Bonds well to a variety of surfaces. This tape is designed to offer a high degree of conformability without excessive stretch. Stiffer backing makes it easier to handle in certain applications.

2 PRODUCT APPLICATION

For patching, sealing, bundling & wrapping.
For splicing and surface protection.

3 GOVERNMENT SPECIFICATION CONFORMANCE

Tested in accordance with UL723 / ASTM E84.

3 NOMINAL VALUES

Tested in accordance with UL723 / ASTM E84.

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	PE Film
Colors	Red
Adhesive	Synthetic Rubber
Adhesion to Steel (oz./in of width) ASTM D-3330	85 (23.3 N/25mm)
Tensile Strength (lbs./in of width) ASTM D-3759	23 (100.7 N/25mm)
Elongation (% at break) ASTM D-3759	75
Total Thickness (mils) ASTM D-3652	7.0 (0.18mm)



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.