

Wall Tac



Available Materials

- High strength nylon

Features/Advantages

- Light to medium loads under dead, variable or vibratory conditions, in solid or hollow environments
- Impervious to moisture
- Quick and easy to install

Concerns

- Drill recommended hole diameter





1055 Nine North Drive, Alpharetta, GA 30004 USA
 1.800.325.7540 / 770.772.7448 / Fax: 1.888.534.8383
www.demandfoamsystems.com / sales@demandfoamsystems.com



Installation

- 1 Drill hole slightly deeper than fastener length. Clean hole of debris.
- 2 Tap "Uni-Tap" into place through material to be fastened.



Order Detail

Order Code	Size	Hole Diameter		Head Diameter	Grip Range	Ultimate Tensile in Shear Load in Lbs.				Box Quantity
		Masonry	Wood/Metal			Tension Hollow Wall	Shear Hollow Material	Tension Cement Block	Head Style	
WT1B	9/32 x 1	1/4"	9/32"	5/8"	3/16-1/2"	130	250	150	TRUSS	6000
WT158B	9/32 x 1 5/8	1/4"	9/32"	5/8"	3/8-1 1/8"	130	253	158	TRUSS	4000
WB218B	9/32 x 2 1/8	1/4"	9/32"	5/8"	7/8-1 5/8"	130	274	154	TRUSS	2500
WT258B	9/32 x 2 5/8	1/4"	9/32"	5/8"	1 3/8-2 1/8"	130	238	163	TRUSS	2000
WT318B	9/32 x 3 1/8	1/4"	9/32"	5/8"	1 7/8-2 5/8"	130	228	150	TRUSS	1500